



AWWA C207 Table 4 Class F Ring (300 psi)

Nominal Size	OD	ID	Thickness	Drilling			Weight
			Slip-On	No. of Holes	Dia. Bolt Holes	Dia. Bolt Circle	lbs.
4	10.00	4.57	1.130	8	0.875	7.88	18
5	11.00	5.66	1.210	8	0.875	9.25	22
6	12.50	6.73	1.310	12	0.875	10.62	30
8	15.00	8.73	1.310	12	1.000	13.00	40
10	17.50	10.88	1.500	16	1.125	15.25	56
12	20.50	12.88	1.630	16	1.250	17.75	83
14	23.00	14.19	1.940	20	1.250	20.25	128
16	25.50	16.19	2.140	20	1.375	22.50	167
18	28.00	18.19	2.250	24	1.375	24.75	204
20	30.50	20.19	2.330	24	1.375	27.00	247
22	33.00	22.19	2.500	24	1.375	29.25	307
24	36.00	24.19	2.690	24	1.625	32.00	388
26	38.25	26.25	3.000	28	1.875	34.50	451
28	40.75	28.25	3.130	28	1.875	37.00	532
30	43.00	30.25	3.150	28	1.875	39.25	586
32	45.25	32.25	3.250	28	1.875	41.50	657
34	47.50	34.25	3.380	28	1.875	43.50	741
36	50.00	36.25	3.460	32	2.125	46.00	802
38	52.25	38.25	3.500	32	2.125	48.00	874
40	54.25	40.25	3.630	36	2.125	50.25	937
42	57.00	42.25	3.810	36	2.125	52.75	1103
44	59.25	44.25	4.000	36	2.125	55.00	1237
46	61.50	46.25	4.130	40	2.125	57.25	1344
48	65.00	48.25	4.500	40	2.125	60.75	1718